

### Overview

The HP StorageWorks Enclosure 4300 is an Ultra3 SCSI disk drive storage enclosure. These enclosures deliver industry-leading data performance, availability, storage density, and upgradability to meet customers' demanding and growing storage needs. The drive carrier is designed to support the fastest current and next generation Ultra3 and Ultra2 hard drives on the same SCSI bus. The ease of upgrading the StorageWorks Enclosure 4200 to the StorageWorks Enclosure 4300 proves to our customers that HP provides the lowest cost of ownership, as well as the fact that technology transitions can be smooth without disrupting critical business environments.

<b>Customer Benefits</b>	<b>Higher Performance</b>	Ultra3 SCSI transfer rates combined with the highest spindle count per U of rack space allows the StorageWorks Enclosure 4300 to achieve the greatest I/Os per second.
	<b>Storage Capacity</b>	3U rack form factor allows customer to achieve the maximum storage capacity per square foot in the data center.
	<b>Upgradability</b>	Ultra3 single and dual I/O upgrade modules make upgrading the StorageWorks Enclosure 4200 to Ultra3 quick and easy.
	<b>Investment Protection</b>	With the ability to upgrade, as well as mix and match, existing Ultra2 components with Ultra3, HP makes technology transitions simple and cost effective, and has simplified the transition to the next generation SCSI protocol.
	<b>Reduced spares inventory</b>	Universal drives and drive carriers across HP's entire Ultra2, Ultra3, and Ultra320 product offering allow the same drives to be used in servers and external storage.

<b>Models</b> (NOTE: See "Configuration Information" for International and Japanese variants)	<b>Model 4314R</b>	Rack-mountable 14 drive enclosure with single bus, single power supply	190209-001
	<b>Model 4314T</b>	Tower 14-bay drive enclosure, single bus, single power supply, LCD monitor	190210-001
	<b>Model 4354R</b>	Rack-mountable 14 drive enclosure with dual bus, dual power supplies	190211-001

<b>Product Family Models:</b>	<p>The hp StorageWorks 4300 Enclosure design allows for specific configurations tailored to the needs of all HP server customers. Three models are available today:</p> <ul style="list-style-type: none"> <li>Model 4314R Rack-mountable 14 drive enclosure with single bus, single power supply</li> <li>Model 4314T Tower mount 14 drive enclosure with single bus, single power supply, LCD monitor</li> <li>Model 4354R Rack-mountable 14 drive enclosure with dual bus, dual power supplies</li> </ul> <p>All models are universal drive enclosures and are supported behind HP Smart Array controllers, HSGx0 controllers, and adapters.</p> <p><b>NOTE:</b> For complete compatibility information, refer to the Specifications section of this document.</p>
-------------------------------	---

<b>Feature List</b>	<ul style="list-style-type: none"> <li>Ultra3 (LVD) data transfer rates (160 MB/s)</li> <li>3U rack height</li> <li>Hot pluggable disk drives, power supplies, and fan pack</li> <li>Redundant fans</li> <li>Redundant power supplies (optional on the 4314R)</li> <li>Single or dual bus I/O</li> </ul>
---------------------	--

### Overview

#### Key Features

**NOTE:** All models of the StorageWorks Enclosure 4300 Family have the following features:

- Ultra3 (LVD) support – Delivering data transfer rates up to 160 MB/s per channel
- 3U rack height
- Supports up to 14 (1-inch) Ultra320 (as well as legacy Ultra3 and Ultra2 drives) Universal hard disk drives
- Provides storage capacity of up to 2TB per enclosure (using 146GB 1-inch disk drives)
- Modular design allows the StorageWorks Enclosure 4300 to be used in any storage configuration from JBOD (Just a Bunch of Disks) to Smart Array storage enclosures to external RAID arrays. Up to 14 enclosures can be mounted in one 42U rack for a single rack storage capacity of up to 28.4TB of disk storage (JBOD configuration) or up to 12 enclosures in an EMA16000 (HSG80 configuration) for a single rack storage capacity of 24.4TB.
- A common storage platform allows for future storage consolidation to the SAN.
- Award-winning innovative SCA (Single Connect Attach) direct connect drive carrier - provides better cooling and reliability for 10K and 15K drives
- Hot pluggable disk drives, power supplies, and fans
- Redundant fans, redundant power supplies and dual bus I/O module (Each Enclosure 4314T and 4314R come with a single power supply that is sufficient to provide power to the enclosure and maintain normal operating levels. A second optional redundant power supply is recommended for higher levels of fault tolerance and availability.)
- Environmental Monitoring Unit (EMU) – Monitors environmental conditions within the enclosure and components such as the power supplies and fans
- Easy removal of parts provides better serviceability. No tools are required!

### Product Highlights

---

<b>Upgradability</b>	Upgrading a StorageWorks Enclosure 4200 to a StorageWorks Enclosure 4300 is as easy as swapping out the I/O module on the back of the unit. The I/O module is warm-swappable, therefore during the upgrade power to the unit can remain on, but all I/O operations need to be stopped to ensure that no data is lost during the upgrade.
<b>Mix and Match</b>	All Ultra320, Ultra3, and Ultra2 devices from HP are compatible with one another so customers can mix and match components in the same storage enclosure or server. When Ultra2, Ultra3, and Ultra320 devices are found on the same Ultra3 SCSI bus, each device will transfer data at its individual interface transfer rate up to the transfer rate of the SCSI bus..  <b>NOTE:</b> For customers who operate legacy Models 4310R and 4350R enclosures, the use of 1-inch Universal Ultra2, Ultra3, or Ultra320 disk drives requires the addition of 0.6-inch drive extenders.
<b>Hot Pluggable</b>	Hot pluggable technology is designed into drives, power supplies and redundant cooling fans. Hot pluggable components can be replaced without powering down the storage system or stopping I/O operations. This feature significantly enhances data availability.
<b>Auto SCSI ID Selection</b>	SCSI ID is automatically set when a drive is inserted into a drive bay.
<b>LED Indicators</b>	Front panel LEDs indicate drive activity, required drive service, and power, giving a quick visual assessment of overall system storage status. LED status and fault indicators for the fans and power supplies are located in the back of the enclosure.
<b>Rack Density</b>	The StorageWorks Enclosure 4300 models have a 3U height.
<b>Environment Monitoring Unit (EMU)</b>	Each StorageWorks Enclosure 4300 model is equipped with an EMU that constantly monitors the enclosure, the power supplies, and fans to ensure suggested operating tolerances are maintained.
<b>Single Bus I/O Module</b>	The single bus I/O module allows one SCSI channel to access all drives in the StorageWorks Enclosure 4300.
<b>Dual Bus I/O Module</b>	The dual bus I/O module allows two SCSI channels to access a single StorageWorks Enclosure 4300. This allows for greater fault tolerance (controller duplexing) or provides access from two different servers to two separate storage areas.
<b>Fault Tolerance</b>	With the dual bus I/O module, redundant power supplies and fans, the StorageWorks Enclosure 4300 family provides a high level of system availability. Using an internal or external RAID Array, the StorageWorks Enclosure 4300 family can be configured for RAID levels 0, 1, 0 + 1, 5.
<b>Manageability</b>	Depending on the host controller, the StorageWorks 4300 Enclosure is managed by HP Insight Manager or StorageWorks Command Console.
<b>Compatibility and Integration Testing</b>	Intensive compatibility and performance testing with HP ProLiant servers and AlphaServers ensures the highest level of integration available in the industry on a HP server. For a complete list of supported HP servers and workstations, please refer to the QuickSpecs and/or User Guide of the array controller or Host Bus adapter that you are planning to use. The list of supported array controllers and SCSI adapters is provided under "Related Options, Controllers

### Product Highlights

---

<b>Product Kit Contents</b>	<b>Model 4314T</b>	Single power supply, single bus I/O module, 14 drive blanks, warranty card, AC power cord, Enclosure 4300 tower user guide, EMU booklet, HP SmartStart CD Kit, documentation CD, and one 12-ft VHDCI to VHDCI SCSI cable:
	<b>Model 4314R</b>	Single power supply, single bus I/O module, 14 drive blanks, warranty card, mounting hardware, Enclosure 4300 user guide, EMU booklet, HP SmartStart CD Kit, documentation CD, and two 12-ft VHDCI to VHDCI SCSI cables (one 110V and one 220V).
	<b>Model 4354R</b>	Redundant power supplies, dual bus I/O module, 14 drive blanks, warranty card, mounting hardware, Enclosure 4300 user guide, EMU booklet, HP SmartStart CD Kit, documentation CD, and two 12-ft VHDCI to VHDCI SCSI cables (one 110V and one 220V).

**NOTE:** A different SCSI cable may be required when the StorageWorks Enclosure 4300 is intended for connection to an HSG80 controller in a Model 2200 controller enclosure or a host-based adapter on an Alpha server. See the Related Options section of this document for cable ordering information.

**NOTE:** To maintain proper cooling and airflow, a drive blank or drive must occupy all bays during operation.

---

### Warranty

StorageWorks Enclosure 4300 family: Three-year limited warranty

**NOTE:** Certain restrictions and exclusions apply. Consult the Customer Support Center at 1-800-345-1518 for details.

Hard drive Pre-Failure Warranty: When used with any one of the StorageWorks Smart Array Family controllers and monitored under HP Insight Manager (v4.20 or later), HP hard drives are supported by a Pre-Failure (replacement) Warranty.

**NOTE:** Pre-Failure Warranty is available on all HP Prosignia™ and HP ProLiant servers using HP Insight Manager v4.20 or later, and covers Pentium® Pro processors, ECC memory, server hard drives, and external storage enclosure hard drives (except the 535 MB Fast-SCSI-2 hard drive) using HP IDA, IDA-2, HP SMART SCSI Array Controllers, HP SMART-2 Array Controllers or HP Smart Array Controllers. Certain restrictions and exclusions apply. Consult the Customer Support Center at: 1-800-345-1518 for details.

### Service And Support, Care Pack and Warranty Information

---

**Software Product Services**

- Standalone telephone support
- Rights to new license version
- Media and documentation updates

---

**Hardware Product Services**

- Installation services
- On-site maintenance (includes warranty support)
- Response time upgrades during the warranty period
- Post-warranty coverage
- RAID setup and performance consulting via statement of work

For additional hardware installation and maintenance information, please refer to the URL listed below:  
[http://www.hp.com/hps/carepack/services/cp\\_installation.html](http://www.hp.com/hps/carepack/services/cp_installation.html)

---

**Warranty Upgrade Options**

- Response – Upgrade on-site response from next business day to same day 4 hours
- Coverage – Extend hours of coverage from 9 hours x 5 days to 24 hours x 7 days
- Duration – Select duration of coverage for a period of 1, 3, or 5 years

---

**Care Pack Information**

Sample part numbers:

- FM-**\*\***XHW-36                      3 year, uplift to 5 x 9, Next Day Response
- FM-**\*\***4HR-36                      3 year, uplift to 5 x 9, 4-hour Response
- FM-**\*\***724-36                      3 year, uplift to 7 x 24, 4-hour Response

**\*\* Represents a two-digit, product-specific code**

Care Pack is defined as an upgrade to the product warranty attribute, available for a specific duration and hours of coverage.

Care Pack is not available for less than the product's warranty duration.

Care Pack is available for sale anytime during the warranty period for most products, but the commencement date will be the same as the Warranty Start Date (delivery date to end user customer). Proof of purchase may be required.

Care Pack services are prepaid.

For additional HP Care Pack Services (hardware & software) information, as well as orderable part numbers, please refer to the URL <http://www.hp.com/hps/carepack/>

---

**Components**

The following brick level options/components do not have individual HP Care Pack Services. These items will be included in product Care Pack Services into which they are installed.

Disk Drives	Tape Drives	CD/DVD ROM	SCSI Hubs in SBBs	Adapters
Bus Converters	Backplane RAID Controllers	Power Supplies	Cabling	Fans

### Configuration Information

Product	Part Number	Shipping Dimensions	UPC Code
StorageWorks Enclosure 4314T	190210-001	25.25 x 12.5 x 23.5 in/64.1 x 31.8 x 59.7 cm	720591469795
StorageWorks Enclosure 4314T (Int'l)	190210-B31		720591469801
StorageWorks Enclosure 4314T (Japan)	190210-291		720591469818
StorageWorks Enclosure 4314R	190209-001	25.25 x 12.5 x 23.5 in/64.1 x 31.8 x 59.7 cm	720591469566
StorageWorks Enclosure 4314R (Int'l)	190209-B31		720591469583
StorageWorks Enclosure 4314R (Japan)	190209-291		720591469788
StorageWorks Enclosure 4354R	190211-001	25.25 x 12.5 x 23.5 in/64.1 x 31.8 x 59.7 cm	720591469825
StorageWorks Enclosure 4354R (Int'l)	190211-B31		720591469832
StorageWorks Enclosure 4354R (Japan)	190211-291		720591469849
Ultra3 Single Bus Upgrade I/O Module	190212-B21	12.75 x 8 x 3.75 in/32.13 x 20.16 x 9.45 cm	720591469856
Ultra3 Dual Bus Upgrade I/O Module	190213-B21	13.25 x 8 x 8.5 in/33.39 x 20.16 x 21.42 cm	720591469863
Redundant Power Supply, 499 watts	338296-B21	3.75 x 8 x 12.75 in/9.52 x 20.32 x 32.38 cm	808736966726
Redundant Power Supply, 499 watts (Int'l)	338296-B22		808736966740
Redundant Power Supply, 499 watts (Japan)	338296-B23		808736966764

### Configuration Information

	Description	Part Number	UPC Code
<b>Controllers &amp; Adapters Supported</b>	HSG80 Controller	176622-B21	720591351335
	<b>NOTE:</b> HSG80 connection to the model 4300 requires the use of the Model 2200 controller shelf: 135820-B21		
	Smart Array 6402	273914-B21	
	Smart Array 5302/128	283552-B21	
	Smart Array 5312	238633-B21	
	Smart Array 5304/256	283551-B21	
	Smart Array 642	291967-B21	
	<b>NOTE:</b> Supported at Ultra2 speeds		
	Smart Array 532	225338-B21	
	Smart Array 5i/5i Plus	N/A	
	<b>NOTE:</b> Single external SCSI channel supported on select ProLiant Servers. See Server QuickSpecs for specific model information.		
	64-bit/133MHz dual channel Ultra320 SCSI Adapter	268351-B21	
	64-bit Dual Channel Wide Ultra3 SCSI Adapter	129803-B21	743172876379
	1 channel Ultra2 (LVD) Adapter (AlphaServer systems)	136237-B21/ SN-KZPCA-AA	743172900562
1 channel Ultra2 (LVD) Adapter (AlphaServer systems)	3X-KZPCA-AA	613326184219	
<b>Power Options</b>	Redundant Power Supply, 499 watts	338296-B21	808736966726
	<b>NOTE:</b> These parts replace 119826-B21 – Redundant power supply, 375 watts)		
	Redundant Power Supply, 499 watts (Int'l)	338296-B22	808736966740
	Redundant Power Supply, 499 watts (Japan)	338296-B23	808736966764
	StorageWorks Enclosure Ultra3 Single Bus I/O Module	190212-B21	720591469856
	StorageWorks Enclosure Ultra3 Dual Bus I/O Module	190213-B21	720591469863
	StorageWorks Enclosure Tower to Rack Conversion Kit	150213-B21	743172948182
	39-ft (12m) VHDCI to VHDCI SCSI Cable	150214-B21	743172948199
	24-ft (7m) VHDCI to VHDCI SCSI Cable	164604-B21	720591275983

### Options

	Description	Part Number	UPC Code
Rack Options	Wide 41U cabinet (Opal)	238789-B21	720591823511
	<b>NOTE:</b> Configuration restrictions apply, please see modular array QuickSpecs for details: <a href="http://h18006.www1.hp.com/storage/arrayssystems.html">http://h18006.www1.hp.com/storage/arrayssystems.html</a>		
	42U Modular Storage Cabinet 60 Hz (Opal)	180311-B21	720591398378
	42U Modular Storage Cabinet 50 Hz (Opal)	180312-B22	720591398590
	36U Modular Storage Cabinet 60 Hz (Opal)	180313-B21	720591398606
	36U Modular Storage Cabinet 50 Hz (Opal)	180314-B22	720591398644
	22U Modular Storage Cabinet 60 Hz (Opal)	180315-B21	720591398651
	22U Modular Storage Cabinet 50 Hz (Opal)	180316-B22	720591398668
	41U Modular Storage Cabinet 60 Hz (Blue)	180317-B21	720591398880
	41U Modular Storage Cabinet 50 Hz (Blue)	180318-B22	720591398897
<b>NOTE:</b> Each Modular Storage Cabinet (42U, 41U, 36U, and 22U) comes with redundant 220 to 240V PDUs and power cables to accommodate Modular Array configurations. For more details on Modular Array solutions, see <a href="http://h18006.www1.hp.com/storage/arrayssystems.html">http://h18006.www1.hp.com/storage/arrayssystems.html</a>			
Legacy Racks Supported	Rack 7142		
	Rack 9142		
	Rack 9136		
	Rack 9122		
	<b>NOTE:</b> Certain power support and cooling restrictions apply when housing a maximum number of Model 4314R or Model 4354R enclosures in one of the supported HP racks. Please refer to <a href="http://h18006.www1.hp.com/storage/index.html">http://h18006.www1.hp.com/storage/index.html</a> for more information or consult the Customer Support Center at 1-800-345-1518 for details.		

	Description	Part Number
Universal SCSI Drives		
Ultra 320 Drives	146.8-GB Pluggable Ultra320 SCSI 10,000 rpm Hard Drive	286716-B22
	72.8-GB Pluggable Ultra320 SCSI 10,000 rpm Hard Drive	286714-B22
	36.4-GB Pluggable Ultra320 SCSI 10,000 rpm Hard Drive	286713-B22
	72.8-GB Pluggable Ultra320 SCSI 15,000 rpm Hard Drive	286778-B22
	36.4-GB Pluggable Ultra320 SCSI 15,000 rpm Hard Drive	286776-B22
	18.2-GB Pluggable Ultra320 SCSI 15,000 rpm Hard Drive "	286775-B22
	0.6-inch (1.52 cm) Drive Extenders (package of 4)	148649-B21
	<sup>(1)</sup> Ultra 2 and Ultra3 drives are also supported in 4300 configurations	
<sup>(2)</sup> For pre-existing 10-bay solutions, drive height extenders are attached to 1 in drives for use in 1.6 in drive bay.		
<b>NOTE:</b> Go to the <a href="http://www.hp.com/products/harddiskdrives">HP SCSI Hard Drive Compatibility table</a> for complete drive compatibility information ( <a href="http://www.hp.com/products/harddiskdrives">http://www.hp.com/products/harddiskdrives</a> ). Using hard drives in unsupported configurations will result in voiding the warranty and could result in damage to the drive and/or loss of data.		
<b>NOTE:</b> This Web site is available in English only.		

### Options

SCSI Cable Options	<i>Cables for use with HSG80 controller in the Model 2200 controller enclosure</i>		
	1M SCSI cable for connection to the Model 2200 Controller Shelf	168256-B21	720591304508
	2M SCSI cable for connection to the Model 2200 Controller Shelf	168257-B21	720591304515
	3M SCSI Cable for connection to the Model 2200 Controller Shelf	188505-B21	743172825544
	<i>Cables for use with Smart Array controllers</i>		
	12 ft VHDCI to 68-pin SCSI Cable	341177-B21	743172660848
	24-ft VHDCI to VHDCI SCSI Cable	164604-B21	720591275983
	39-ft VHDCI to VHDCI SCSI Cable	150214-B21	743172948199
	<i>Cables for use with the KZPCA-AA host bus adapter</i>		
	1M SCSI 68HD Cable	BN38C-01	None
	2M SCSI 68HD Cable	BN38C-02	None
	3M SCSI 68HD Cable	BN38C-03	None
	5M SCSI 68HD Cable	BN38C-05	None
	10M SCSI 68HD Cable	BN38C-10	None

### Technical Specifications

<b>Protocol Support</b>	Wide Ultra3 (LVD) Wide Ultra2 (LVD)
<b>O/S Support</b>	Defined by specific HP array controller or SCSI adapter used; please refer to the QuickSpecs and/or User Guide of the specific array controller or SCSI adapter
<b>Dimensions (HxWxD)</b>	Tower 22.5 x 13.25 x 23 in/56.7 x 33.9 x 57.96 cm Rack 5.2 x 19 x 20.5 in/13.1 x 47.88 x 51.66 cm
<b>Shipping Dimensions (HxWxD)</b>	Tower 34.25 x 14.5 x 31.25 in/86.31 x 36.54 x 78.75 cm Rack 34.25 x 14.5 x 31.25 in/86.31 x 36.54 x 78.75 cm Redundant Power Supply 3.75 x 8.0 x 12.75 in/9.52 x 20.32 x 32.38 cm
<b>Weight</b>	Tower 93 lb/42.8 kg Rack 68 lb/30.9 kg Redundant Power Supply 6.6 lbs/3.0 kg
<b>LED Indicators (on front panel)</b>	EMU Status LED (left) Enclosure Power LED (middle) Fault LED (right)
<b>Drive LED Indicators (on drive trays)</b>	Drive LED (top) On Line LED (middle) Drive Failure LED (bottom)
<b>Enclosure LED Indicators (back of unit)</b>	I/O Module (top) EMU (middle) Power supplies (bottom)
<b>Input Requirements</b>	Nominal Line Voltage 110 to 240 V AC Range Line Voltage 90 to 264 V AC Line Frequency 47 to 63 Hz Typical Input Current 2.3A at 120 V AC
<b>Relative Humidity (non-condensing)</b>	Operating 10% to 90% Shipping 5% to 90%
<b>Controllers and Adapters Supported Models 4314T, 4314R, 4354R</b>	Smart Array 6402 Smart Array 5302/128 Smart Array 5312 Smart Array 5304/256 Smart Array 642 <b>NOTE:</b> Supported at Ultra2 speeds Smart Array 532 Smart Array 5i/5i Plus <b>NOTE:</b> Single external SCSI channel supported on select ProLiant Servers. See Server QuickSpecs for specific model information. HSG80 Controller HSG60 Controller 64-bit Dual Channel Wide Ultra3 SCSI Adapter 1 channel Wide Ultra2 Adapter (AlphaStations) 1 channel Wide Ultra2 Adapter (AlphaServer systems) <b>NOTE:</b> See your server and controller compatibility matrix for details on controller and server compatibility.

### Technical Specifications

I/O Module Connector	Very High Density Cable Interconnect (VHDCI)	
Power	377 Watts per supply (load)	
BTU (220 volts)	Single power supply 14 drives	1164 BTUs/hour
	Single power supply 5 drives	536 BTUs/hour
	Single power supply 1 drive	273 BTUs/hour
	Dual power supply 14 drives	1232 BTUs/hour
	Dual power supply 5 drives	625 BTUs/hour
	Dual power supply 1 drive	352 BTUs/hour
Temperature Range	Operating	50° to 94° F/10° to 35° C°
	Shipping	-40° to 151° F/-40° to 66° C

**NOTE:** To maintain proper cooling and airflow, a drive blank or drive must occupy all bays during operation.

© Copyright 2003 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

Windows, NT, and Windows Datacenter 2000 are U. S. registered trademarks of Microsoft Corporation. UNIX is a registered trademark of The Open Group. All other product names mentioned herein may be trademarks of their respective companies.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.